

GUIDE WIRES

- Packed in see-through packs of 10
- Non-Sterile

LENGTH	POINT STYLE	WIRE DIAMETER											
		1.0mm	1.1mm	1.2mm	1.4mm	1.6mm	2.0mm	2.4mm					
MM	INCH												
230	9	Trocar/Blunt	600-0911-D	600-0911-E	600-0911-F	600-0911-T	600-0911-G	600-0911-H	600-0911-I				
230	9	Blunt/Blunt	600-0912-D	600-0912-E	600-0912-F	600-0912-T	600-0912-G	600-0912-H	600-0912-I				
254	10	Trocar/Blunt	600-1011-D	600-1011-E	600-1011-F	600-1011-T	600-1011-G	600-1011-H	600-1011-I				
254	10	Blunt/Blunt	600-1012-D	600-1012-E	600-1012-F	600-1012-T	600-1012-G	600-1012-H	600-1012-I				
305	12	Trocar/Blunt	600-1211-D	600-1211-E	600-1211-F	600-1211-T	600-1211-G	600-1211-H	600-1211-I				
305	12	Blunt/Blunt	600-1212-D	600-1212-E	600-1212-F	600-1212-T	600-1212-G	600-1212-H	600-1212-I				
380	15	Trocar/Blunt	600-1511-D	600-1511-E	600-1511-F	600-1511-T	600-1511-G	600-1511-H	600-1511-I				
380	15	Blunt/Blunt	600-1512-D	600-1512-E	600-1512-F	600-1512-T	600-1512-G	600-1512-H	600-1512-I				
460	18	Trocar/Blunt	600-1811-D	600-1811-E	600-1811-F	600-1811-T	600-1811-G	600-1811-H	600-1811-I				
460	18	Blunt/Blunt	600-1812-D	600-1812-E	600-1812-F	600-1812-T	600-1812-G	600-1812-H	600-1812-I				

Threaded Guide Wires are available on wires with trocar points 1.6mm diameter and above in thread lengths of 5, 10 & 15mm. To order these, add desired thread length to end of product REF above, e.g 600-0911-G15 has 15mm thread.

SWITCHING STICKS

LENGTH	POINT STYLE	WIRE DIAMETER					
		3.0mm	3.2mm	3.5mm	4.0mm	4.5mm	5.0mm
MM	INCH						
330	13	Bullet/Bullet	600-1313-L	600-1313-M	600-1313-N	600-1313-O	600-1313-P
356	14	Bullet/Bullet	600-1413-L	600-1413-M	600-1413-N	600-1413-O	600-1413-P

CANNULATED SLEEVES

Cannulated Sleeves to suit guide wires are available upon request.