


NEEDLE ELECTRODES



300-450-A Scale 1:1



300-450-E Scale 1:1



BULLET

300-460-C Scale 1:1

PRODUCT NUMBER	DESCRIPTION
300-450-A	25mm (1") Fine Needle on 50mm (2") shaft
300-450-D	25mm (1") Fine Needle on 75mm (3") shaft
300-450-E	25mm (1") Fine Needle on 100mm (4") shaft
300-450-F	25mm (1") Fine Needle on 125mm (5") shaft
300-450-G	25mm (1") Fine Needle on 150mm (6") shaft
300-450-H	25mm (1") Fine Needle on 175mm (7") shaft
300-450-I	25mm (1") Fine Needle on 200mm (8") shaft
300-450-J	25mm (1") Fine Needle on 225mm (9") shaft
300-455-A	6mm (¼") Fine Needle on 50mm (2") shaft
300-455-B	12mm (½") Fine Needle on 50mm (2") shaft
300-455-C	12mm (½") Fine Needle Insulated Tip on 50mm (2") shaft
300-460-A	6mm (¼") Bullet Point Needle (Heavy Duty) on 50mm (2") shaft
300-460-B	12mm (½") Bullet Point Needle (Heavy Duty) on 50mm (2") shaft
300-460-C	25mm (1") Bullet Point Needle (Heavy Duty) on 50mm (2") shaft

Electrode shank diameter is standard 2.38mm (3/32")